

FEATURES:

- Integrates with LoRaWAN HUB to log, display, control, and trend data from WPT Network
- Built-in web pages for direct access to data and trending
- Each GBC supports up to 100 WPT's
- Create and manage setpoint change schedules
- Built-in BACnet/IP connectivity for integration with existing Building Automation Systems
- Alarm notifications via emails
- Stores up to one month of historical data
- Easy to mount on wall
- Fanless low-power design
- Supports dual 10 / 100/ 1000 Mbps Ethernet ports
- Windows 10 Pro Operating System, configurable for client security policy
- ROHS Compliant



Network and Data Controller for Cypress EnviroSystems WPT networks. Use to make data available to existing building automation systems, or use standalone with the WPT Web interface.

The Green Box Controller (GBC) is a flexible communications gateway that logs data from the Cypress EnviroSystems WPT network and provides it to users and building automation systems through a variety of interfaces.

For users with existing building automation systems and operator workstations, it provides data over BACnet/IP for seamless integration and transparent co-existence with direct digital control systems.

For users which do not need to connect to existing infrastructure, the Green Box Controller can also provide data directly to users via a standalone web interface accessible via a web browser from any computer. Alarm notification may be sent to any email address, which may be routed to any cell phone via text message.

KEY PRODUCT SPECIFICATIONS:

User Interface:	Built-in web pages for easy web browser access to control, data and trending
Available Data Protocols:	BACnet/IP for building Ethernet LAN; RESTful API
Mobile Access:	Alarm notification via email or text message
Approvals:	ROHS compliant; certified by US Federal GSA for use on US Gov't networks
Power Supply:	Input: 90-264VAC, 36W; Output: DC 12V @ 3A
Humidity:	10% - 90%, non-condensing
Operating Temperature:	-4°F to 131°F (-20°C to 55°C)
Storage Temperature:	-4°F to 131°F (-20°C to 55°C)
Vibration Endurance:	3 Grms (5 – 500Hz, X Y, Z directions)
Dimensions:	Length – 7.87 in (200mm) Width – 4.72 in (120mm) Depth – 1.81 in (46mm)
Weight:	3.97lb (1.8kg)

HEADQUARTERS

6830 via del Oro, Suite 100

San Jose, CA 95119

+1 800 544-5411

www.CypressEnviroSystems.com

info@CypressEnviroSystems.com

Cypress EnviroSystems and its logo are trademarks of Cypress EnviroSystems, Inc. The name of any other company, products, or services mentioned herein are for identification purposes only and may be trademarks or service marks of or may be copyrighted by their respective holders.